




# MianKang Bearing Co., Ltd.



7310 becbp Bearing 2D drawings and 3D CAD models

## skf 7310 becbp bearing

Bearing No. 7310 becbp

Size	110x50x27 mm
Bore Diameter	110 mm
Outer Diameter	50 mm
Width	27 mm
d	50 mm
D	110 mm
B	27 mm
d <sub>1</sub>	73.8 mm
d <sub>2</sub>	61.13 mm
D <sub>1</sub>	88.8 mm
a	47 mm
r <sub>1,2</sub> - min.	2 mm
r <sub>3,4</sub> - min.	1 mm
d <sub>a</sub> - min.	61 mm
D <sub>a</sub> - max.	99 mm
D <sub>b</sub> - max.	104 mm
r <sub>a</sub> - max.	2 mm
r <sub>b</sub> - max.	1 mm
Basic dynamic load rating - C	75 kN
Basic static load rating - C <sub>0</sub>	51 kN
Fatigue load limit - P <sub>u</sub>	2.2 kN
Reference speed	8000 r/min
Limiting speed	8000 r/min
Calculation factor - k <sub>r</sub>	0.1
Calculation factor - k <sub>a</sub>	1.6



## MianKang Bearing Co., Ltd.

Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - Y <sub>0</sub>	0.52
Calculation factor - Y <sub>1</sub>	0.55
Calculation factor - Y <sub>2</sub>	0.93
Calculation factor - X	0.35
Calculation factor - Y <sub>0</sub>	0.26
Calculation factor - Y <sub>1</sub>	
Calculation factor - Y <sub>2</sub>	0.57
Category	Angular Contact Ball Bearings
Inventory	4.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.04
EAN	7316577092526
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3   ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	50MM Bore; 110MM



## MianKang Bearing Co., Ltd.

	Outside Diameter; 27MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3   ISO P6; No Filling Slot; No Snap Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	7310 BECBP
Weight / LBS	2.288
Outside Diameter	4.331 Inch   110 Millimeter
Bore	1.969 Inch   50 Millimeter
Width	1.063 Inch   27 Millimeter
bore diameter:	50 mm
radial static load capacity:	51 kN
outside diameter:	110 mm
cage material:	Nylon
overall width:	27 mm
outer ring width:	27 mm
contact angle:	40 °
maximum rpm:	8000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	2 mm



## MianKang Bearing Co., Ltd.

radial dynamic load capacity:	75 kN
series:	73
$d_1$	73.8 mm
$d_2$	61.13 mm
$D_1$	88.8 mm
$r_{1,2}$ min.	2 mm
$r_{3,4}$ min.	1 mm
$d_a$ min.	61 mm
$D_a$ max.	99 mm
$D_b$ max.	104 mm
$r_a$ max.	2 mm
$r_b$ max.	1 mm
Basic dynamic load rating C	75 kN
Basic static load rating $C_0$	51 kN
Fatigue load limit $P_u$	2.16 kN
Calculation factor A	0.0418
Calculation factor $k_r$	0.1
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor $Y_0$	0.26
Calculation factor $Y_2$	0.57
Calculation factor X	0.57
Calculation factor $Y_0$	0.52
Calculation factor $Y_1$	0.55
Calculation factor $Y_2$	0.93
Mass bearing	1.1 kg